



## BOKI



Туре	ceiling luminaire
item nr.	15/1745.19/9292
GTIN (EAN)	4022671106610

## description

BOKI, ceiling luminaire, nickel mat - chrome, LED replaceable by specialist, direct/indirect, IP20

material and dimensions		
color	nickel mat - chrome	
material	steel + shade, anthracite	
dimensions	D 450 mm x H 115 mm	
weight	2.75 kg	

light and electric specifications     lightsource   LED replaceable by specialist     control   dimmable trailing/leading edge     Casambi   optionally available with CASAMBI control     system demand   31 W     net   2,280 lm (luminaire/net)     gross   3,510 lm (LED-module/gross)     light color   2,800 K     CRI   90-100     light emission   direct/indirect     degree of protection   IP20     protection class   1     Product type according to EU   containing product     2019/2020   Energy efficiency class of the built-in light source(s)     F   accessory			
controldimmable trailing/leading edgeCasambioptionally available with CASAMBI controlsystem demand31 Wnet2,280 lm (luminaire/net)gross3,510 lm (LED-module/gross)light color2,800 KCRI90-100light emissiondirect/indirectdegree of protectionIP20protection class1Product type according to EU2019/2015 and EU2019/2020containing productEnergy efficiency class of the built-in light source(s)F	light and electric specifications		
controledgeCasambioptionally available with CASAMBI controlsystem demand31 Wnet2,280 lm (luminaire/net)gross3,510 lm (LED-module/gross)light color2,800 KCRI90-100light emissiondirect/indirectdegree of protectionIP20protection class1Product type according to EU2019/2015 and EU2019/2020containing productEnergy efficiency class of the built-in light source(s)F	lightsource	LED replaceable by specialist	
Casambioptionally available with CASAMBI controlsystem demand31 Wnet2,280 lm (luminaire/net)gross3,510 lm (LED-module/gross)light color2,800 KCRI90-100light emissiondirect/indirectdegree of protectionIP20protection class1Product type according to EU2019/2015 and EU2019/2020containing productEnergy efficiency class of the built-in light source(s)F	control	0 0	
Casambi   CASAMBI control     system demand   31 W     net   2,280 lm (luminaire/net)     gross   3,510 lm (LED-module/gross)     light color   2,800 K     CRI   90-100     light emission   direct/indirect     degree of protection   IP20     protection class   1     Product type according to EU   2019/2015 and EU     2019/2020   containing product     Energy efficiency class of the built-in light source(s)   F		edge	
CASAMBI controlsystem demand31 Wnet2,280 lm (luminaire/net)gross3,510 lm (LED-module/gross)light color2,800 KCRI90-100light emissiondirect/indirectdegree of protectionIP20protection class1Product type according to EUcontaining product2019/2015 and EUcontaining product2019/2020F	Casambi		
net2,280 lm (luminaire/net)gross3,510 lm (LED-module/gross)light color2,800 KCRI90-100light emissiondirect/indirectdegree of protectionIP20protection class1Product type according to EU2019/2015 and EU2019/2020containing productEnergy efficiency class of the built-in light source(s)F		CASAMBI control	
gross 3,510 lm (LED-module/gross)   light color 2,800 K   CRI 90-100   light emission direct/indirect   degree of protection IP20   protection class 1   Product type according to EU 2019/2015 and EU   2019/2020 containing product   Energy efficiency class of the built-in light source(s) F	system demand	31 W	
light color 2,800 K   CRI 90-100   light emission direct/indirect   degree of protection IP20   protection class 1   Product type according to EU 2019/2015 and EU   2019/2020 containing product   Energy efficiency class of the built-in light source(s) F	net	2,280 lm (luminaire/net)	
CRI 90-100   light emission direct/indirect   degree of protection IP20   protection class 1   Product type according to EU 2019/2015 and EU   2019/2020 containing product   Energy efficiency class of the built-in light source(s) F	gross	3,510 lm (LED-module/gross)	
light emission direct/indirect   degree of protection IP20   protection class 1   Product type according to EU 2019/2015 and EU   2019/2020 containing product   Energy efficiency class of the built-in light source(s) F	light color	2,800 K	
degree of protection IP20   protection class 1   Product type according to EU 2019/2015 and EU   2019/2020 containing product   Energy efficiency class of the built-in light source(s) F	CRI	90-100	
protection class 1   Product type according to EU 2019/2015 and EU   2019/2020 containing product   Energy efficiency class of the built-in light source(s) F	light emission	direct/indirect	
Product type according to EU 2019/2015 and EU 2019/2020 Energy efficiency class of the built-in light source(s)	degree of protection	IP20	
2019/2015 and EU containing product   2019/2020 Energy efficiency class of the built-in light source(s)	protection class	1	
2019/2020 Energy efficiency class of the built-in light source(s)	Product type according to EU		
Energy efficiency class of the built-in light source(s)	2019/2015 and EU containing product		
built-in light source(s)	2019/2020		
built-in light source(s)	Energy efficiency class of the		
accessory	built-in light source(s)	F	
accessory			
	accessory		

name	CASAMBI CBU-TED Bluetooth Dimmer
item nr.	6100
short text	CASAMBI, accessory