



## **BONO**



Туре	floor luminaire
item nr.	17/2501.70
GTIN (EAN)	4022671120654

## description

Indirect light is distributed evenly through the opal glass sphere, while an additional LED with reflector provides homogeneous direct reading light.

The indirect light and reading light can be switched and dimmed individually or together using the integrated sensor switch.

luminaire head rotatable and tiltable

BONO, floor luminaire, coffee, LED replaceable by specialist, direct/indirect, IP20

material and dimensions	
color	coffee
material	aluminium + Opalglas weiss
dimensions	L 333 mm x B 250 mm x H 1,410 mm
weight	3.4 kg
light and electric specifications	
lightsource	LED replaceable by specialist
control	integrated dimmer
system demand	8 W
	2001 (1 1 1 1 1)

CONTROL	integrated diminier
system demand	8 W
net	890 lm (luminaire/net)
gross	1,120 lm (LED-module/gross)
light color	2,700 K
CRI	90-100
light emission	direct/indirect
degree of protection	IP20
protection class	2
Product type according to EU	
2019/2015 and EU	containing product
2019/2020	
Energy efficiency class of the	F
built-in light source(s)	_

www.helestra.de data sheet 17/2501.70 last updated 30.04.2025 errors and changes excepted