



\$\text{C} \text{\te}\text{\texi}\text{\text{\text{\text{\text{\text{\text{\text{\texi}\text{\text{\texit{\tex{\text{\text{\text{\text{\text{\texi}\text{\text{\texit{\text{\ti

## **PONT**



Туре	ceiling luminaire
item nr.	25/2080.22
GTIN (EAN)	4022671113083

## description

The surface mounted PONT luminaires feature an adjustable beam angle from 15 -  $45^{\circ}.$ 

Spots are 355° rotatable and 80° tiltable.

The clear glass lens can optionally be equipped with a special diffusing foil, altering the light effect from a sharp beam to a diffuse beam with soft edges.

PONT, ceiling luminaire, mat black, LED replaceable by specialist, direct, IP20

material and dimensions	
color	mat black
material	aluminium + glass lense
dimensions	L 250 mm x B 85 mm x H 170 mm
weight	1.6 kg
light and electric specifications	
lightsource	LED replaceable by specialist
control	dimmable trailing/leading edge
system demand	19 W

	edge	
system demand	19 W	
net	1,140 lm (luminaire/net)	
gross	1,960 lm (LED-module/gross)	
light color	2,700 K	
CRI	90-100	
beam angle	45 °	
light emission	direct	
degree of protection	IP20	
protection class	1	
Product type according to EU		
2019/2015 and EU	containing product	
2019/2020		
Energy efficiency class of the	F	
built-in light source(s)		

www.helestra.de data sheet 25/2080.22 last updated 30.04.2025 errors and changes excepted